

FILE HARDJP3.DOC
041029-CSP

5/7/1
DIALOG(R)File 351:Derwent WPI
(c) 2004 Thomson Derwent. All rts. reserv.

001819582

WPI Acc No: 1977-40569Y/*197723*

Fibre reinforced refractory construction material - prepd. by coating
porous substrate e.g. gypsum board with aq. cement slurry contg. glass
fibre

Patent Assignee: KANEBO LTD (KANE)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 52051719	A	19770425				197723 B

Priority Applications (No Type Date): JP 75126542 A 19751020

Abstract (Basic): JP 52051719 A

The fire-proofing and heat-resisting material exhibits no cracking and peeling-off, has no water-absorbability or -permeability, and good physical strength. It is used in construction for inner walls, outer walls, partitioning plate, roofing material and floors etc.

The material comprising a porous base material e.g. gypsum board, MgCO₃ plate, foamed concrete, perlite plate, asbestos-perlite plate, foamed polystyrene and polyurethane foam etc. A thin layer of an aq. cement slurry and alkali-resistant glass fibre, e.g. coated with a Zr salt or containing ZrO₂ etc. the amt. of which is 2 to 15 wt. % based on the amt. of the cement, are coated into the material.

Derwent Class: A13; A25; A93; L02; Q43; Q44

International Patent Class (Additional): E04B-001/94; E04C-002/06